



Antique Douglas Fir Scar'dFace Flooring

October 1, 2009

product information

the wood for the Antique Douglas Fir Scar'dFace product usually comes from joists and timbers salvaged from old lumber mills and warehouses; the flooring will have a milled face which reveals the beautiful color and texture of the wood with its striking grain patterns; a knots dance throughout the floor along with a few nail holes surrounded by ferrous bleed from the nails themselves

specie

primarily Douglas Fir

source :: antique 100% recycled

industrial salvage

moisture content

kiln-dried to 6-8% moisture content

hardness

janka hardness rating: 700

character rating

our character rating: 5.6 (ample character)

our character scale rates floors on a 1 - 10 scale; a low number is a refined floor and a high number is very rustic

grading

the appearance standards outlined here apply to a floor as a whole and not to individual boards

knots

knots are limited to 2" diameter and smaller with no more than one knot per square foot of flooring; some knots may be broken

holes

occasional nail holes allowed, many with ferrous bleed; rarely bolt holes may be included

cracks/checks

moderate surface checking is allowed; cracks through the thickness of the board are not allowed

color

color variation are unlimited, but predominately range from amber to tan and yellow

grain

the majority of the wood will be flat or cathedral grain; some rift cut or quarter sawn boards may be included

millwork

¾" thick; the tongue and groove will be milled on the edges; the back of the board is milled with back outs; the ends of the boards will be cut square

widths

3" to 8" milled to the full inch wide with custom sizes available; floors are usually produced with a combination of 3 or more face sizes with enough of each size to create a random pattern

lengths

1' through 10'; with an average length of about 6'; boards up to 12' included if available

surface

the face is planed smooth

installation

basic principles of installation for solid wood floors apply to this product and it should be installed according to the standard professional practices of your area; although, installers should be well experienced with custom wood floors and have artistic skill in board placement

unfinished

this flooring product comes unfinished and is designed to be prepped and finished on site