

Antique Tobacco Oak PatinaDeep Engineered Flooring

May 4, 2011



Design Professionals to specify this product use the following information:

product: Antique Tobacco Oak PatinaDeep Engineered Flooring (designate appropriate face widths)

contact: HistoricWoods by LunarCanyon 801-835-3476 kyle@historicwoods.net

Product Description:

1. **specie** a combination of red & white oak
2. **source** :: **antique** 100% recycled primarily siding from tobacco barns
3. **moisture content** wear layer kiln-dried to 6-8% moisture content
4. **hardness** janka hardness rating: 1290
5. **our character rating:** 7.9 (rustic) our character scale rates floors on a 1 - 10 scale; a low number is a refined floor and a high number is very rustic
6. **grading** the appearance standards outlined here apply to a floor as a whole and not to individual boards
7. **knots** an unlimited amount of knots of any size are allowed; some knots are broken or missing
8. **holes** an unlimited amount of nail holes are allowed; generally there are only a few per board & many boards will not have any
9. **check/cracks** an unlimited amount of surface checking is allowed; some cracks are allowed
10. **exposed platform** some knots, holes & cracks will show the black adhesive on the platform which can be left as-is or filled during installation, depending on customer preference
11. **color** the face color will usually vary from dark brown and gray (almost black when finish is applied) to light golden brown and tans; an unlimited combination of colors is allowed
12. **grain** the majority of the wood will be flat or cathedral grain; some rift cut or quarter sawn boards may be included
13. **surface** the face will be skip-planed, wire-brushed (to remove dirt, debris and loose wood; texture is added in some areas; due to the variance in texture some boards may be higher (over wood) than the board next to it; over wood can be deflected in the screening process after installation; occasionally some joints will need additional work with hand tools to feather the higher board down to the board next to it
14. **millwork** 5/8" thick at the milled portions of the face with the original textured areas thinner; the platform is 12mm thick & the wear layer about 5/32" thick; a tongue and groove will be milled on the edges; the back of the board is smooth with back outs; the ends of the boards will be cut square

Antique Tobacco Oak PatinaDeep Engineered Flooring

May 4, 2011



15. **widths** 4" to 7" face width with custom sizes available; floors are usually produced with a combination of 3 or more face sizes with enough of each size to create a random pattern
16. **lengths** 1' through 10'; with an average length of about 5'; boards up to 12' included if available
17. **installation** basic principles of installation for engineered wood floors apply to this product and it should be installed according to the standard professional practices of your area; although, installers should be well experienced with custom wood floors and have artistic skill in board placement
18. **unfinished** this flooring product comes unfinished and is designed to be prepped and finished on site